

# OmniPlanter™

## 5.25

OmniPlanter™  
5.25



### Specifications: OmniPlanter™ 5.25

### Mounting hardware included

|                                    |   |
|------------------------------------|---|
| Nominal Impedance                  | 4 ohm   |
| Impedance (min)                    | 4 ohm   |
| Sensitivity dB @ 2.83V/1M          | 91 dB   |
| Sensitivity dB @ 1W/1M (2)         | 88 dB   |
| Frequency Response ( $\pm 3$ dB)   | 76 Hz - 19 kHz  |
| Frequency Response ( $\pm 10$ dB)  | 65 Hz - 19 kHz  |
| Max. Program Power                 | 140W  |
| Max. Continuous Power RMS          | 70W   |
| Max. Power SPL @ 1 M               | 106.5 dB  |
| Tap Selector                       | Wire Leads  |
| Transformer Options                | 25v / 70v / 100v  |
| Transducer - Low Frequency Driver  | 5.25" Coax  |
| Transducer - High Frequency Driver | .75" Dome   |
| Colors                             | Grey Granite, Terra Cotta   |
| Tweeter - part                     | .75" Dome   |
| Inputs                             | wire leads  |
| Height (SM = Height)               | 35.6 mm / 14"   |
| Diameter (SM = Width)              | 40.6 mm / 16"   |
| Weight                             | 5.4 Kg / 12 lb  |
| Shipping Weight                    | 11.3 kg / 25 lb   |
| Owner's Manual - color             | <a href="#">Download Owners Manual</a>  |
| Regulatory - CE                    | approved  |
| Regulatory - RoHS                  | approved  |
| Applications                       | Perfect for hardscaping, the OmniPlanter 5.25 can be used on patios, near pools, in outdoor dining settings or in courtyards. |

---

# OmniPlanter™

## 5.25

OmniPlanter™  
5.25



---

### Description

The OmniPlanter 5.25 hides a 2-way speaker inside a functional planter with a 16" diameter bowl. Drainage holes in the planter help to ensure healthy plants and will not damage the speaker below. As the name suggests, the speaker provides omnidirectional (360 degrees horizontal) coverage. OmniPlanters are constructed of UV-stable, rotation-molded polyethylene and are available in two colors.

### Applications

Perfect for hardscaping, the OmniPlanter 5.25 can be used on patios, near pools, in outdoor dining settings or in courtyards.

### Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which

explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

### Technical Data and Specification Tools

#### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com).

Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

#### Data Acquisition and

### Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

### Architectural Specifications

No specifications currently.

#### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<http://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.

---

# OmniPlanter™

## 5.25

OmniPlanter™  
5.25

