



## Specifications: Coconutz

## Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4 ohm
Sensitivity dB @ 2.83V/1M	91dB
Sensitivity dB @ 1W/1M (2)	88dB
Frequency Response ( $\pm 3$ dB)	86 Hz - 19 kHz
Frequency Response ( $\pm 10$ dB)	76 Hz - 19 kHz
Max. Program Power	150W
Max. Continuous Power RMS	75W
Power Output	75 Watts
Max. Power SPL @ 1 M	106.5 dB
Transducer - Low Frequency Driver	5.25" Coax
Transducer - High Frequency Driver	.75" Dome
Colors	Brown
Height (SM = Height)	311.15 mm / 12.25 in
Diameter (SM = Width)	177.8 mm / 7 in
Owner's Manual - color	<a href="#">Download Owners Manual</a>
Regulatory - CE	approved
Applications	Suspend the CocoNutz near pools or over patios, "tiki bars", outdoor cafes and other settings.

## Description

This 5.25" coaxial hanging speaker blends in perfectly with any tropical theme. Designed to resemble a large coconut, both in texture and color, the 2-way, 75 watt CocoNutz has a 5.25" coax woofer and .75" dome tweeter. Note: This speaker does not accommodate plants.

## Applications

Suspend the CocoNutz near pools or over patios, "tiki bars", outdoor cafes and other settings.

## Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

## Technical Data and Specification Tools

### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA,

TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<http://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.