

# Pavarocci™ SweetSpot

Pavarocci™  
SweetSpot



## Specifications: Pavarocci™ SweetSpot

## Mounting hardware included

|                                  |  |
|----------------------------------|--|
| Nominal Impedance                | 4 ohm                                  |
| Impedance (min)                  | 4.0 ohm                                |
| Sensitivity dB @ 2.83V/1M        | 91.5dB                                 |
| Sensitivity dB @ 1W/1M (2)       | 88.5dB                                 |
| Frequency Response ( $\pm 3$ dB) | 62 Hz - 20 kHz                         |
| Max. Program Power               | 140w                                   |
| Max. Continuous Power RMS        | 70w                                    |
| Max. Power SPL @ 1 M             | 107.0dB                                |
| Tap Selector                     | Wire leads                             |
| Tweeter - part                   | .75" Dome                              |
| Driver - part                    | 8" Dual Voice Coil                     |
| Inputs                           | Wire lead                              |
| Height (SM = Height)             | 317.5 mm / 12.50 in                    |
| Diameter (SM = Width)            | 406.4 mm / 16.00 in                    |
| SM Depth (Including Bracket)     | 13.50 in                               |
| Weight                           | 10.9 kg / 24 lbs                       |
| Accessories Optional             | Security Bracket (RSB1)                |
| Owner's Manual - color           | <a href="#">Download Owners Manual</a> |

## Applications

The versatile Pavarocci can be used almost anywhere: pools, patios, hot tub areas, courtyards, outdoor cafes, outdoor malls, theme parks, zoos and more.

# Pavarocci™ SweetSpot

Pavarocci™  
SweetSpot



## Key Features

- One coaxial 8.0 inch (203.2 mm) weather resistant low frequency driver and one 1.0 inch (25 mm) weather resistant, high frequency driver.
- UV-, scratch-, chlorine- and weather- resistant enclosure with professional- grade components for long-lasting performance and durability.
- Extremely versatile 70 watt speaker for use in any size space.
- Exotic look of weathered sedimentary rock.
- Color options: brown, gray or sandstone.

## Description

This popular rock combines a weathered sedimentary look with a powerful 2-way design. Ideal for providing separation of left and right channels in a single enclosure, the Pavarocci SweetSpot has a dual voice coil 8" woofer and dual ¾" tweeters. Its size and sonic performance make it highly versatile for a wide range of outdoor applications.

## Applications

The versatile Pavarocci can be used almost anywhere: pools, patios, hot tub areas, courtyards, outdoor cafes, outdoor malls, theme parks, zoos and more.

## Patented Rockustics Technologies

All Rockustics cabinets are constructed from a non-polluting stone and resin compound. The cabinets maintain a natural aesthetic, weather and age naturally, and are an earth-friendly alternative to plastic construction. To ensure 100% water- and weatherproofing, all Rockustics products come as a sealed unit. Therefore, the inclusion of optional transformers must occur prior to completion by manufacturer. Rockustics and MSE Audio constantly develops new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents. MSE Audio actively defends its patents in order to protect

Rockustics resellers and end users.

## Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

## Technical Data and Specification Tools

### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and

---

# Pavarocci™ SweetSpot

Pavarocci™  
SweetSpot



downloads include: EASE™  
data - 3-D polar plots.  
EASE™ Address - 2-D  
modeling for distributed  
systems Autodesk® Revit®  
software Tech Sheets -  
Technical information and  
architectural specs for  
system engineers  
SoundTubeSPEC™ -  
Proprietary speaker  
placement software

## Data Acquisition and Verification

All data for SoundTube  
speakers are independently  
collected from and verified  
by NWAALabs  
([www.nwaalabs.com](http://www.nwaalabs.com)) using  
their proprietary MACH  
testing system. All data are  
collected and analyzed  
according to ASTM, ISO and  
AES standards using EASRA,  
TEF and MLSSA. Full  
balloon data including both  
phase and magnitude are  
compiled into a variety of  
formats including EASE 4.x,  
GLL and CLF.

## Architectural Specifications

The loudspeaker shall be an  
on-ground coaxial design  
consisting of one 203.2 mm  
(8.0 in) low-frequency  
transducer and one 25 mm

(1.0 in.) tweeter. The low-  
frequency voice coil  
diameter shall be 25 mm  
(1.0 in). Performance  
specifications of a typical  
production unit shall be as  
follows: Usable frequency  
response shall extend from  
68 Hz - 22 kHz. Measured  
sensitivity (2.83 Volt input, 1  
meter) shall be at least 91.5  
dB. The loudspeaker shall  
have a nominal impedance of  
4 Ohms. The enclosure shall  
be constructed of a non-  
polluting elastomer  
reinforced resin polymer  
with pulverised stone. Color  
options shall be brown, gray  
or sandstone. All  
transducers and network  
circuitry are weather  
resistant and ship in a sealed  
enclosure. The external  
wiring input connector shall  
be hardwire leads. The  
overall cabinet dimensions  
shall be no more than 406  
mm (16.0 in) in width by  
342.9 mm (13.5 in) in height  
and 317.5 mm (12.5 in.) in  
depth. The unit shall weigh  
no more than 10.9 kG (24  
lbs). The system shall be the  
Pavarocci for both low and  
high impedance  
applications.

## Rockustics

8005 W 110th Street, Suite  
208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<http://rockustics.mseaudio.com>  
All SoundTube products come  
with a 5-year limited warranty.

---

# Pavarocci™ SweetSpot

---

Pavarocci™  
SweetSpot



## Optional Accessories



**Security Bracket (RSB1)**