

OmniPlanter™ 8.0 SweetSpot

OMNIPLANTER™
8.0 SWEETSPOT



Specifications: OmniPlanter™ 8.0 SweetSpot

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4 ohm
Sensitivity dB @ 2.83V/1M	92 dB
Sensitivity dB @ 1W/1M (2)	89 dB
Frequency Response (± 3 dB)	75 Hz - 19 kHz
Frequency Response (± 10 dB)	55 Hz - 20 kHz
Max. Program Power	150 Watts
Max. Continuous Power RMS	75 Watts
Power Output	75 Watts
Max. Power SPL @ 1 M	109.0 dB
Transducer - Low Frequency Driver	8" Dual Voice Coil
Transducer - High Frequency Driver	(2) .75" Soft Dome
Colors	Gray Granite or Terra Cotta
Tweeter - part	(2) .75" Soft Dome
Height (SM = Height)	508 mm / 20"
Diameter (SM = Width)	609.6 mm / 24"
Weight	9.1 Kg / 20 lb
Shipping Weight	11.3 kg / 25 lb
Owner's Manual - color	Download Owners Manual
Regulatory - CE	approved
Regulatory - RoHS	approved
Applications	Use the OmniPlanter 8.0 SweetSpot in large gardens and courtyards, outdoor restaurants, hotels, shopping malls, and theme parks

OmniPlanter™ 8.0 SweetSpot

OMNIPLANTER™
8.0 SWEETSPOT



Description

This 24" diameter (610mm) planter with drainage holes easily accommodates a selection of live plants while providing omnidirectional (360 degrees horizontal) audio coverage. Its two way design includes a dual voice coil 8" coax woofer and two .75" dome tweeters.

OmniPlanters are constructed of UV-stable, rotation-molded polyethylene and are available in two colors.

Applications

Use the OmniPlanter 8.0 SweetSpot in large gardens and courtyards, outdoor restaurants, hotels, shopping malls, and theme parks

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics

dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube

speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<http://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

OmniPlanter™ 8.0 SweetSpot

OMNIPLANTER™
8.0 SWEETSPOT

