

XT-SurroundStone 5

XT-SURROUNDSTONE™
5



Specifications: XT-SurroundStone 5

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4.0 ohm
Sensitivity dB @ 2.83V/1M	87.0dB
Sensitivity dB @ 1W/1M (2)	84.0dB
Frequency Response (± 3 dB)	70 Hz - 20 kHz
Frequency Response (± 10 dB)	60 Hz - 22 kHz
Max. Program Power	150w
Max. Continuous Power RMS	75w
Max. Power SPL @ 1 M	103.0dB
Tap Selector	5-Position Rotary Switch w/ Transformer Bypass Position
Transformer Options	25/70.7/100 V w/ 8 Ω Bypass
Transducer - Low Frequency Driver	5.25" Polypropylene Cone w/ Butyl Rubber Surround
Transducer - High Frequency Driver	.75" Silk Dome
Colors	Brown, Grey, Sandstone
Tweeter - part	.75" Silk Dome
Inputs	Wire lead
Height (SM = Height)	317.5 mm / 12.5"
Diameter (SM = Width)	381 mm / 15.0"
Weight	18.2 kg / 40.1 lb
Shipping Weight	20.0 kg / 44 lb
Accessories Optional	Security Bracket (RSB1)
Owner's Manual - color	Download Owners Manual
Regulatory - CE	approved
Applications	The XT-SurroundStone 5 will provide discreet, omnidirectional music and paging in amusement parks, zoos, gardens and outdoor shopping plazas.

XT-SurroundStone

5

XT-SURROUNDSTONE™
5



Description

Designed to provide omnidirectional audio for outdoor commercial settings, this rock speaker includes a 64 watt transformer for use in 70V systems. It incorporates a 5.25" coax woofer and .75" dome tweeter in a sealed, on-ground enclosure, and is available in three colors.

Applications

The XT-SurroundStone 5 will provide discreet, omnidirectional music and paging in amusement parks, zoos, gardens and outdoor shopping plazas.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order

to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH

testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite
208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<http://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

XT-SurroundStone 5

XT-SURROUNDSTONE™
5



Optional Accessories



Security Bracket (RSB1)