



## Specifications: PunkSub™

## Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4 ohm
Sensitivity dB @ 2.83V/1M	89dB
Sensitivity dB @ 1W/1M (2)	86dB
Frequency Response (± 3 dB)	60 - 100 Hz
Frequency Response (±10 dB)	45 - 100 Hz
Max. Program Power	400 W
Max. Continuous Power RMS	200 W
Power Output	100 Watts Per Driver
Max. Power SPL @ 1 M	109.0 dB
Tap Selector	Wire Leads
70.7 Volt Transformer Taps	120 W / 107.0 dB
100 Volt Transformer Taps (dB)	120 W / 107.0 dB
25 Volt Transformer Taps (dB)	15 W / 98.0 dB
Transformer Options	25/70.7/100 V
Transducer - Low Frequency Driver	8" Woofers
Colors	Brown, Gray or Sandstone
Driver - part	8" Woofers
Height (SM = Height)	292.1 mm / 11.5"
Diameter (SM = Width)	533.4 mm / 21"
Weight	38.6 kg / 85 lb
Shipping Weight	39.6 kg / 87 lb
Accessories Optional	120 watt XFMR, Security Bracket (RSB1)
Owner's Manual - color	<a href="#">Download Owners Manual</a>
Regulatory - CE	approved
Applications	Bring powerful bass to gardens, patios, pool areas, restaurants, theme parks or other outdoor settings.

## Description

This 200 watt subwoofer is designed to accept full-range left and right inputs and drive two satellite speakers in addition to the subwoofer. Two 8" subwoofers are incorporated in a durable, weathered rock enclosure, one for each side of a stereo source. A passive crossover system is included.

## Applications

Bring powerful bass to gardens, patios, pool areas, restaurants, theme parks or other outdoor settings.

## Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

## Technical Data and Specification Tools

### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA,

TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<http://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.

## Optional Accessories

**120 watt XFMR**



**Security Bracket (RSB1)**