

XT-SurroundStone 8

XT-SURROUNDSTONE™
8



Specifications: XT-SurroundStone 8

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4.0 ohm
Sensitivity dB @ 2.83V/1M	91.0dB
Sensitivity dB @ 1W/1M (2)	88.0dB
Frequency Response (\pm 3 dB)	38 Hz - 22 kHz
Max. Continuous Power RMS	100 Watts
Max. Power SPL @ 1 M	106.5dB
Tap Selector	Wire leads
Transformer Options	25/70.7/100 V w/ 8 Ω Bypass
Colors	Brown, Grey, Sandstone
Grille - material	N/A
Inputs	Wire lead
Height (SM = Height)	355.6 mm / 14.00 in
Diameter (SM = Width)	438.2 mm / 17.25 in
SM Depth (Including Bracket)	292.1 mm / 11.5 in
Weight	23.9 kg / 52.69 lb
Accessories Optional	Security Bracket (RSB1)
Owner's Manual - color	Download Owners Manual
Regulatory - CE	N/A
Applications	Use the XT-SurroundStone 8 in theme parks, large amusement parks, courtyards, shopping plazas and any other outdoor setting requiring omnidirectional music and paging.

XT-SurroundStone 8

XT-SURROUNDSTONE™
8



Description

The XT-SurroundStone 8 is ideal for large commercial outdoor installations, with inconspicuous yet encompassing sound. An 8" coax woofer and and .75" dome tweeter are incorporated in a sealed, on-ground enclosure with omnidirectional dispersion. A 64 watt transformer is provided for use in 70V systems. Available in three colors.

Applications

Use the XT-SurroundStone 8 in theme parks, large amusement parks, courtyards, shopping plazas and any other outdoor setting requiring omnidirectional music and paging.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which

explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube

speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite
208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<http://rockustics.mseaudio.com>
All SoundTube products come
with a 5-year limited warranty.

XT-SurroundStone 8

XT-SURROUNDSTONE™
8



Optional Accessories



Security Bracket (RSB1)