



Specifications: XT-PowerRock™

Mounting hardware included

| | |
|------------------------------------|--|
| Nominal Impedance | 8 ohm |
| Impedance (min) | 8.0 ohm |
| Sensitivity dB @ 2.83V/1M | 97.0dB |
| Sensitivity dB @ 1W/1M (2) | 97.0dB |
| Frequency Response (± 3 dB) | 45 Hz - 20 kHz |
| Max. Program Power | 250w |
| Max. Continuous Power RMS | 125w |
| Max. Power SPL @ 1 M | 118.0dB |
| Tap Selector | Wire leads |
| Transducer - Low Frequency Driver | 8" High-Efficiency Woofer |
| Transducer - High Frequency Driver | 1.3" (1" throat) Compression Driver |
| Colors | Brown, Grey, Sandstone |
| Inputs | Wire lead |
| Height (SM = Height) | 450.9 mm / 17.75 in |
| Diameter (SM = Width) | 438.15 mm / 17.25 in |
| SM Depth (Including Bracket) | 368.3 mm / 14.50 in |
| Weight | 21.8 kg / 48.06 lb |
| Accessories Optional | Security Bracket (RSB1) |
| Regulatory - CE | N/A |
| Applications | Ideal for outdoor commercial settings, the XT-PowerRock is also suited for use in large residential gardens and other areas where extended sonic coverage is required. |

Description

Designed for long throw and high intelligibility, the XT-PowerRock is the ideal choice for theme parks and other large outdoor settings. Its granite exterior is matched with an 8" high-efficiency woofer and 1.3" compression driver, with 250 watts of power handling. A built-in 120 watt transformer makes it easy to incorporate the XT-PowerRock into 70V systems.

Applications

Ideal for outdoor commercial settings, the XT-PowerRock is also suited for use in large residential gardens and other areas where extended sonic coverage is required.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively

defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are

collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<http://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

Optional Accessories



Security Bracket (RSB1)