



Specifications: PunkSub™

Mounting hardware included

| | |
|-----------------------------------|---|
| Nominal Impedance | 4 ohm |
| Impedance (min) | 4 ohm |
| Sensitivity dB @ 2.83V/1M | 89dB |
| Sensitivity dB @ 1W/1M (2) | 86dB |
| Frequency Response (± 3 dB) | 60 - 100 Hz |
| Frequency Response (± 10 dB) | 45 - 100 Hz |
| Max. Program Power | 400 W |
| Max. Continuous Power RMS | 200 W |
| Power Output | 100 Watts Per Driver |
| Max. Power SPL @ 1 M | 109.0 dB |
| Tap Selector | Wire Leads |
| Transformer Options | 25/70.7/100 V |
| Transducer - Low Frequency Driver | 8" Woofers |
| Colors | Brown, Gray or Sandstone |
| Driver - part | 8" Woofers |
| Height (SM = Height) | 292.1 mm / 11.5" |
| Diameter (SM = Width) | 533.4 mm / 21" |
| Weight | 38.6 kg / 85 lb |
| Shipping Weight | 39.6 kg / 87 lb |
| Accessories Optional | 120 watt XFMR, Security Bracket (RSB1) |
| Regulatory - CE | approved |
| Applications | Bring powerful bass to gardens, patios, pool areas, restaurants, theme parks or other outdoor settings. |

Description

This 200 watt subwoofer is designed to accept full-range left and right inputs and drive two satellite speakers in addition to the subwoofer. Two 8" subwoofers are incorporated in a durable, weathered rock enclosure, one for each side of a stereo source. A passive crossover system is included.

Applications

Bring powerful bass to gardens, patios, pool areas, restaurants, theme parks or other outdoor settings.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA,

TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<https://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

Optional Accessories

120 watt XFMR



Security Bracket (RSB1)