

Surroundstone™ 5

SURROUNDSTONE™
5



Specifications: Surroundstone™ 5

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4.0 ohm
Sensitivity dB @ 2.83V/1M	87.0 dB
Sensitivity dB @ 1W/1M (2)	84.0 dB
Frequency Response (± 3 dB)	60 Hz - 20 kHz
Frequency Response (± 10 dB)	53 Hz - 20 kHz
Max. Program Power	150w
Max. Continuous Power RMS	75w
Max. Power SPL @ 1 M	103.0dB
Tap Selector	Wire leads
Transducer - Low Frequency Driver	5.25" Polypropylene
Transducer - High Frequency Driver	.75" Dome
Colors	Brown, Grey, Sandstone
Tweeter - part	.75" Dome
Driver - part	5.25" Coax
Inputs	Wire lead
Height (SM = Height)	317.5 mm / 12.5"
Diameter (SM = Width)	381.0 mm / 15.0"
Weight	18.2 kg / 40.0 lb
Shipping Weight	21.8 kg / 48 lb
Accessories Optional	65 WATT XFMR, Security Bracket (RSB1)
Regulatory - CE	approved
Applications	Use the SurroundStone 5 in residential gardens and outdoor living areas.

Description

This premium 2-way speaker provides high-performance sound with omnidirectional (360 degrees horizontal) coverage. It incorporates a 5.25" coax woofer and .75" dome tweeter in a sealed, on-ground enclosure, and is available in three colors.

This model is only available in limited quantities.

Applications

Use the SurroundStone 5 in residential gardens and outdoor living areas.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed

according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<https://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

Surroundstone™ 5

SURROUNDSTONE™
5



Optional Accessories

65 WATT XFMR



Security Bracket (RSB1)